



AirULTRA-R /

	AirULTRA-R 3	AirULTRA-R 4	AirULTRA-R 5
	3.9 mm	4.6 mm	5.2 mm
LED	SMD	SMD	SMD
	65536 /m ² 16384 /	46,656 /m ² 11,664 /	36,864 /m ² 9, 216 /
(W×H)(mm)	250 × 250	250 × 250	250 × 250
(W×H×D)(mm)	500 × 500 × 86	500 × 500 × 86	500 × 500 × 86 *
/ (W×H)	2 × 2	2 × 2	2 × 2
(W×H)	64 × 64	54 × 54	48 × 48
(W×H)	128 × 128	108 × 108	96 × 96
	7.9 kg/	7.9 kg/	7.9 kg/
	31.6 kg/m ²	31.6 kg/m ² *	31.6 kg/m ² *
	14 - 16 bit	14 - 16 bit	14 - 16 bit
	281 trillion	281 trillion	281 trillion
	4000 : 1	4000 : 1	4000 : 1
	55 - 92 w/	55 - 92 w/	55 - 92 w/
	184 w/	184 w/	184 w/
	-30 - 50 / 10% - 90%	-30 - 50 / 10% - 90%	-30 - 50 / 10% - 90%
	-30 - 60 / 10% - 95%	-30 - 60 / 10% - 95%	-30 - 60 / 10% - 95%
	5000 nits	5000 nits	5000 nits
	3840 Hz	3840 Hz	3840 Hz
	140°	140°	140°
	120°	120°	120°
LED	100000 Hrs	100000 Hrs	100000 Hrs
	20	20	20
	16	16	16
(-: ;+:)	-10°/-5°/0°/+5°	-10°/-5°/0°/+5°	-10°/-5°/0°/+5°
IP	IP 65	IP 65	IP 65
	CE, EMC ClassA, ETL, RoHS *	CE, EMC ClassA, ETL, RoHS *	CE, EMC ClassA, ETL, RoHS *

*

